



FILTRATION PRODUCT

SAFEDEFLO C600 PLATE & FRAME DE PACKAGE

Filtration equipment

OVERVIEW

TETRA SafeDEflo Compact 600 plate and frame diatomaceous earth (DE) filtration package is designed to filter brines, chemicals, and produced water in completion, stimulation, and workover operations. The SafeDEflo C600 package is recommended for well volumes up to 500 barrels when higher flow rates and a more compact unit is needed.

SafeDEflo UDW systems are sized to offer flow rates between 8 and 10 bbl/min, while offering optimal hydraulic filtration performance. Actual field performance may vary due to brine composition, density and solids type and concentration.

Our SafeDEflo filtration packages include the following: filter press, auxiliary skid, diesel driven centrifugal pump, and 200 feet of hose with connections and guard filter. All of the SafeDEflo filtration equipment is skid mounted. The presses all have blowdown capability, stainless steel manifolds, and gasketed plates. Additionally, they allow manual override of the hydraulics system.

SYSTEM ADVANTAGES

- ▶ Multiple components provide configuration flexibility, allowing most efficient use of rig space.
- ▶ Can be used on smaller rigs.
- ▶ Can supply higher flow rates due to inline manifold system.
- ▶ Four corner discharge plates.
- ▶ 1,200 mm plates versus 1,000 mm plates to allow for a more compact unit.
- ▶ More economical (lower day rate) than larger units.

EQUIPMENT SPECIFICATIONS

Unit Size

600 sq ft

Flow Rate

8 to 10 bbl/min

Density Range

8.4 to 12.5 lb/gal

Footprint

16'L x 15'W

COMPACT 600 SQUARE FOOT PLATE AND FRAME DE PACKAGE

FILTER UNIT

Length	10.58 ft	Filter Area	600 sq ft
Width	5.25 ft	Maximum Net Filter Volume	29.9 cu ft
Height	7.0 ft	Plate Size	1,200 mm
Weight	12,000 lbs	Maximum Differential Pressure	80 psi

PRECOAT / BODY FEED UNIT

Length	6.5 ft	Precoat Tank	10 bbls
Width	5.25 ft	Body Feed Tank	6 bbls
Height	7.0 ft		
Weight	4,000 lbs		

PUMP SKID

Length	8.33 ft	Discharge	4 in
Width	4.08 ft	Suction	4 in
Height	6.25 ft	Power	100 hp with air start
Weight	3,800 lbs	Maximum Operating Pressure	125 psi

GUARD UNIT (DUAL POD, PARALLEL OPERATION)

Length	5.3 ft	Maximum # of Cartridges	64
Width	4.5 ft	Cartridge Length	40 in
Height	5.5 ft	Net Filter Area	1,408 sq ft
Weight	1,500 lbs		

SAFEDEFLO PACKAGE OPERATIONAL REQUIREMENTS

- ▶ All TETRA SafeDEflo Packages require 120 cfm at 100 psi.



Contact us to learn more at: www.onetetra.com

Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. Further, nothing contained herein shall be taken as a recommendation to manufacture or use any of the herein described materials or processes in violation of existing or future patents.