

PRODUCTION TESTING & FLOWBACK PRODUCT

SURFACE SAFETY VALVE

OVERVIEW

The surface safety valve is an independent safety valve controlled by the Emergency Shut Down system. Positioned upstream of the choke manifold, it is the primary safety valve on any production operation. Connected through the Emergency Shut Down system panel, it can be activated by overpressure, loss of pressure, high or low vessel levels or manual intervention.

APPLICATIONS

- ▶ Offshore and onshore operations.
- ▶ Emergency well shutdown valve, fail close / pump open.
- ▶ Well test operations.
- ▶ Flow back operations.
- ▶ Wellsite intervention services.
- ▶ Early production facilities and extended appraisal testing.

FEATURES

- ▶ Hydraulic or Pneumatic variants.
- ▶ Normally closed.

BENEFITS

- ▶ Can be tied into numerous shut down functions via the ESD panel.
- ▶ API 6A and NACE compliant.



PRODUCTION TESTING & FLOWBACK PRODUCT

SURFACE SAFETY VALVE

SPECIFICATIONS

Working Pressure	10,000, 15,000 psig
Temperature	-20/350°F (-29°/177°C)
Applicable Code	NACE MR-01-75/API 6A
Actuators	Pneumatic or Hydraulic
Connections	
Inlet Union (Female)	2" to 4" - 1502 to 2202 or API flanges
Outlet Union (Male)	2" to 4" - 1502 to 2202 or API flanges
Dimensions	3'L x 2'W x 5'H
Weight	85/230 lbs

Note: Various sizes and configurations available.



Emergency Shutdown Panel



Contact us to learn more at: www.onetetra.com

Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. Further, nothing contained herein shall be taken as a recommendation to manufacture or use any of the herein described materials or processes in violation of existing or future patents.