

# WELLBORE CLEANUP & DISPLACEMENT PRODUCT

## TETRA ADVANCECLEAN COMBO TOOL

### OVERVIEW

The TETRA AdvanceClean Combo Tool combines brushes and scrapers to offer the benefits of both. The scrapers are designed to mechanically scour mud cake, cement sheaths, pipe scale, perforation burrs, and other restrictive material from wellbore casing interior wall surfaces, while the brushes assist the scraper, polish casing surfaces, agitate the circulating fluid and enhance cleaning performance. It can be run as an integral part of the drill-string to scrape and brush the casing wall as the pipe is run in hole as part of most drilling/milling/polishing assemblies, as a stand-alone device or with other down-hole tools as part of the clean-up system.

Six scraper pads and six brush pads are mounted within the mandrel, offering 360° of casing altogether. Installed in each brush pad are six rows of bristles. The spring-activated pads are forced outwards against the casing wall. The pad pressure can be customized to well geometry. The mandrel housing the pads acts as one piece and rotates with the pads. This tool can be rotated within torque restrictions and reciprocated without fear of damage to the casing or to the tool itself. While running in hole, it is good practice to break circulation and reciprocate the pipe regularly every 5,000 ft to disperse and enhance the clean-up of debris build-up.

### FEATURES AND BENEFITS

- ▶ Robust, durable design.
- ▶ One-piece mandrel.
- ▶ 360° Casing Coverage.
- ▶ Spring Loaded Scraper Blades and Brush Pads.
- ▶ 4145 Materials of Construction.
- ▶ 6 5/8" through 13 3/8" Casing Sizes.
- ▶ Effective removal of mud cake, cement sheaths, and pipe scale.

Model	Casing Range	API Connection	Length	Bore	Tool Weight	Created Weight
TA-700-C	6 5/8" thru 8 5/8"	3 1/2" IF or 3 1/2" REG	77 1/4"	1 1/2"	228 lbs	246 lbs
TA-900-C	8 5/8" thru 13 3/8"	4 1/2" IF	85 3/4"	2 1/2"	531 lbs	573 lbs

### DESIGN SPECIFICATIONS

- Description**  
Combo Tool
- Current Model Numbers**  
TA-700-C, TA-900-C
- Sizes Available**  
See table below
- Material**  
4145
- Temperature Rating**  
Not limited
- Maximum Rotational Speed**  
90 RPM
- Maximum RIH/POOH Speed**  
150 ft/min
- Thread Connections**  
See table below



Contact us to learn more at: [www.onetetra.com](http://www.onetetra.com)

Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. Further, nothing contained herein shall be taken as a recommendation to manufacture or use any of the herein described materials or processes in violation of existing or future patents.