

# COMPLETION FLUIDS AND ADDITIVES PRODUCT

## TETRA CS NEPTUNE DIVALENT FLUIDS

High-density, solids-free completion fluids.

### OVERVIEW

TETRA CS Neptune divalent completion fluids are innovative, high-density, solids-free, zinc-free, and formate-free fluids for offshore and complex wells, including high-temperature applications, that require heavy clear brines to control well pressure during the completion phase. TETRA CS Neptune fluids are an environmentally friendly, cost-effective alternative to traditional zinc bromides and cesium formate high-density completion fluids. They were designed for use in well completion and workover operations, but can also be formulated as a low-solids reservoir drill-in fluid (DIF).

TETRA CS Neptune family of fluids consist of divalent and monovalent completion fluids. See the table on the next page for complete portfolio details.

### FEATURES

- ▶ TETRA CS Neptune divalent fluids can be formulated to densities up to 17.5 lb/gal, 2.10 sg (and work is underway to extend the limits). See the table on the next page for complete portfolio features.
- ▶ Can exhibit significantly lower TCT and PCT than equivalent-density calcium bromide brines.
- ▶ Stable at elevated temperatures and during storage.
- ▶ Can be mixed with standard clear brine fluid mixing equipment.
- ▶ Compatible with downhole elastomers and metallurgies
- ▶ Exhibits compatibility similar to that of calcium bromide with other working and reservoir fluids.
- ▶ Formulated from renewable products, ensuring continuity of supply.

### BENEFITS

- ▶ Zinc-free and priority pollutants-free, and therefore, do not require a zero-discharge system of work.
- ▶ Can be reclaimed for reuse, using standard technology.
- ▶ Neutral to alkaline in pH, thereby posing low health and safety risks to rig site and plant personnel.
- ▶ Lower unit cost than alternative fluid chemistries.
- ▶ Requires no special mixing, handling, or storage equipment at the rig site.
- ▶ Environmentally acceptable globally.

### SPECIFICATIONS

#### Appearance

Clear to amber liquid

#### Odor

Odorless

#### Density

14.3 to 17.5 lb/gal

#### Acidity

pH 7-10

#### Water Solubility

Soluble

#### Recommended Treatment

TETRA CS Neptune fluids are delivered in bulk form.

# COMPLETION FLUIDS AND ADDITIVES PRODUCT

## TETRA CS NEPTUNE DIVALENT FLUIDS

Continued

### APPLICATION INFORMATION

TETRA CS Neptune divalent fluids are formulated predominantly using halide-based brines and a complex, proprietary blend of additives which achieves significant reductions in the true crystallization temperature (TCT) and pressure crystallization temperature (PCT) of the fluid. Each TETRA CS Neptune fluid is formulated specifically for the density and TCT/PCT requirements of the project. Advice on formulation and use of TETRA CS Neptune fluids should always be sought from the TETRA Innovation Group.

### SAFETY AND HANDLING

Please refer to the product's Safety Data Sheet.

### TETRA CS NEPTUNE FLUIDS PORTFOLIO FEATURES

#### TETRA CS Neptune Divalent Completion Fluids

- Density range up to 15.4 lb/gal or 1.84 sg
- Temp stability to 350°F / 177°C
- Field proven

#### TETRA CS Neptune HDD Completion Fluids (High Density Divalent)

- Provide density extension to 15.7 lb/gal or 1.88 sg
- Temp stability to 290°F / 143°C
- Drill-in and low solids invert emulsions
- Patents granted or pending

#### TETRA CS Neptune XHDD Completion Fluids (Extra High Density Divalent)

- Densities up to 17.5 lb/gal or 2.10 sg

#### TETRA CS Neptune HDM Completion Fluids (High Density Monovalent)

- Density range up to 13.1 lb/gal or 1.57 sg
- Temp stability to > 350°F / 177°C
- Drill-in, low solids invert emulsions, and frac fluids
- Patents granted or pending

#### TETRA CS Neptune XHDM Completion Fluids (Extra High Density Monovalent)

- Density range up to 15.7 lb/gal or 1.88 sg
- Temp stability to > 350°F / 177°C
- Drill-in, low solids invert emulsions, and frac fluids



Visit us to learn more at: [www.onetetra.com](http://www.onetetra.com)

You are responsible for determining whether products and the information in this document are appropriate for your use and for ensuring that your workplace and disposal practices are in compliance with applicable laws and other governmental enactments. TETRA assumes no obligation or liability for the information in this document. No freedom from infringement of any patent owned by TETRA or others is to be inferred. The product shown in this literature may not be available for sale and/or available in all geographies where TETRA is represented. As such, the claims made may not have been approved for use in all countries. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. IN NO CASE SHALL THE DESCRIPTIONS, DATA OR DESIGNS PROVIDED BE PRESUMED TO BE A PART OF OUR TERMS AND CONDITIONS OF SALE.