

COMPLETION FLUIDS & ADDITIVES PRODUCT

TETRA SWEEP VISCOSIFIER

Polymer

OVERVIEW

A high strength, liquefied proprietary polymer in a light hydrocarbon-based oil, TETRA SWEEP viscosifier is suited for use in most completion and workover fluids. It is used as a primary viscosifier and suspending agent for hole cleaning applications. TETRA SWEEP viscosifier is specifically designed for Frac Plug debris, including metal slips, TETRA SWEEP viscosifier also aids coil operations through its friction reducing characteristics. The liquid formulation provides superior dispersability and general ease of handling. It is degradable by time, oxidizing agents, enzymes and extreme temperatures.

APPLICATIONS

TETRA SWEEP is a versatile product and can be used in most types of clear brine fluids for rheology modification, hole cleaning, and solids suspension. It provides excellent friction reduction for coiled tubing operations and is useful over a wide pH range. TETRA SWEEP is uniquely stable and easily handled.

FEATURES AND BENEFITS

- ▶ Mixes well in low-shear environments and is complimented by the TETRA SWEEP CMP.
- ▶ Extremely stable suspension provides reliable properties.
- ▶ Performs well in fresh water, seawater, brine and saturated salt environments.
- ▶ Disperses rapidly without “fisheyes”.
- ▶ Provides a wide range of viscosities for hole cleaning and removal of Frac Plug debris.
- ▶ Easy to handle.

RECOMMENDED TREATMENT

- ▶ TETRA SWEEP can be used in a variety of applications, and recommended volumes range from 0.06 gal/bbl to 1.20 gal/bbl.

SAFETY AND HANDLING

- ▶ Please refer to the product’s Safety Data Sheet.

PHYSICAL PROPERTIES

Appearance

Tan viscous liquid

pH

7.0

Specific Gravity

1.02

Incompatibilities

Heat

Flash Point

335°F (168°C)

Viscosity

4,000-5,000 DV-II+

Water Solubility

Dispersible

PACKAGING INFORMATION

5 gal pail

32 pails per pallet



Contact us to learn more at: www.onetetra.com

Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer’s use and for ensuring that Customer’s workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. Further, nothing contained herein shall be taken as a recommendation to manufacture or use any of the herein described materials or processes in violation of existing or future patents.